



ULTRA-PRO



ULTRA-PRO Pressure Tanks

Application: potable water, flush water, pumps and booster sets

Technical and Dimensional Data

Vertical Models with Galvanized Flanges / Stainless Steel Flanges								
Model	Code	Capacity (Litres)	Ø Diameter (mm)	H Height (mm)	E (mm)	Max. Pressure (bar)	Precharge (bar)	Connection
ULTRA-PRO 60 V	1100006012	60	380	860	170	10	1,5	1"G
ULTRA-PRO 100 V	1100010012	100	450	910	153	10	1,5	1"G
ULTRA-PRO 200 V	1100020012	200	550	1235	210	10	1,5	1 ½"G
ULTRA-PRO 300 V	1100030012	300	630	1365	188	10	1,5	1 ½"G
ULTRA-PRO 500 V	1100050012	500	750	1560	188	10	1,5	1 ½"G
ULTRA-PRO 750 V	1100075012	750	750	2075	150	10	1,5	1 ½"G
ULTRA-PRO 1000 V	1100100012	1000	850	2100	120	10	1,5	1 ½"G

Material Description

Description	Material
Shell	Carbon Steel
Membrane	Butyl*
Colour	Epoxy-polyester Powder Red

*Replaceable membrane for alimentary purposes

Operating Conditions

Max. operating pressure	10 bar
Operating temperatures	-10 ~ +99 °C
Factory precharge	1.5 - 2 bar

Technical Drawings

